

## ALUJET Alucral

### Product- discription

- ▶ ALUJET Alucral adhesive tape is used to make airtight joints at overlapping areas of vapour check membranes. Through the use of a solvent-free acrylate adhesive, joints are possible from -5°C upwards. If ALUJET Alucral adhesive tape is used correctly, a vapour check function is also ensured in the overlapping area.



Fig. 1: ALUJET Alucral

### Product benefits

- ▶ According DIN 4108-11 (Klebeband KB); extremely high adhesive strength; modified acrylate dispersion; solvent-free; handy dimensions.

### Area of application

- ▶ Commercially-available vapour checks; wood; hard wooden composite boards; gypsum fibreboards; gypsum plasterboards.

### Technical data

Test	Standard	Unit	Value
Substrate			Special paper
Adhesive			Acrylat
Backing			Siliconised paper
Temperature resistance		°C	-40 bis +90
Processing temperature		°C	From -5 upwards
Thickness	DIN EN 1942	mm	0,29 ±0,05
Elongation	DIN EN 14410	%	>5
Breaking force	DIN EN 14410	N / 10 mm	65
Adhesion on steel	DIN EN 1939	N / 10 mm	14

### Specification

- ▶ Roll width: 60 mm
- ▶ Roll length: 41 m
- ▶ Carton content: 8 rolls
- ▶ Pallet content: 54 carton

### Storage

- ▶ At approx. 15 °C to 30 °C and max. 65% rel. humidity.

**Processing**

▶ Remove the ALUJET Alucral from the backing paper and affix centrally on the overlap. Tape the overlap bit by bit using the ALUJET Alucral. A permanently airtight bond is created by pressing the tape down onto the substrate. The substrate must be structurally stable and dry, and must be free from dust, grease and any adhesive residues.




Fig. 2: Overlapping inside

**Notes**


Our instructions for use, guidelines for use, product and service information and other technical specifications only serve as a guide, they only describe the properties of our products (value specifications/determinations at time of production) and services and do not constitute guaranteed characteristics. Owing to the wide-ranging areas of application of the individual products and the particular conditions (e.g. usage parameters, material properties etc.), it is incumbent on the user to test our products. Our applications engineering consulting - whether verbal, in writing or by way of tests is offered free of charge and is not legally binding.