

ALUJET Isotape

Product description

▶ ALUJET Isotape consists of a PVC soft foil backing and is used to bond overlapping joints on pipe cladding foils such as ALUJET Isofol SE. The colour of the material is largely adapted to the ALUJET Isofol SE, ALUJET insulating sheet and moulded ALUJET pieces to achieve the maximum possible colour fastness. ALUJET Isotape can also be used for electrical and cable insulations.



Fig. 1: ALUJET Isotape

Product benefits

▶ Extremely high adhesive strength; Versatile and adaptable
Easy to use

Technical data

Test	Standard	Unit	Value
Substrate			Soft PVC
Materialstärke		mm	0,15
Elongation		%	150
Adhesive strength		N / 25mm	approx. 5
Reaction to fire	DIN 4102		B1
Tensile elongation		N / 25 mm	approx. 50
Temperatur resistance		°C	-45° to +105

Specification

▶ Roll width: 19 mm 25 mm 30 mm 50 mm
Roll length: 25 m 25 m 25 m 25 m
Carton content: 32 rolls 24 rolls 20 rolls 12 rolls

Lagerung

▶ 12 month, from +15°C to +30°C und max. 65% rel. humidity

Hinweise



Our instructions for use, guidelines for use, product and service information and other technical specifications only serve as a guide, they only describe the properties of our products (value specifications/determinations at time of production) and services and do not constitute guaranteed characteristics. Owing to the wide-ranging areas of application of the individual products and the particular conditions (e.g. usage parameters, material properties etc.), it is incumbent on the user to test our products. Our applications engineering consulting - whether verbal, in writing or by way of tests is offered free of charge and is not legally binding.